

HIGEN		INDUCTION MOTOR DATA SHEET		160 kW 6 P 315M	
MODEL:		CUSTOMER :		COIL SPEC NO.:	
APPLICATION:		PROJECT NAME:		REV. NO : 0	
				QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		315M		OUTPUT 160 kW	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 6 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-Δ	
PROTECTION		IP 55		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> REACTOR ( %TAP) <input type="checkbox"/> V.V.V.F	
PHASE		3 PHASE		<input type="checkbox"/> VECTOR-DRIVE	
SERVICE FACTOR		1.15		RATED VOLTAGE 380 V V	
INSULATION CLASS		F CLASS		FREQUENCY 60 Hz	
TEMP. RISE AT FULL LOAD (at S.F 1.0)		CURRENT			
RES. METHOD		105 deg		NO LOAD A A	
THERMO. METHOD		°C		FULL LOAD 297.5 A A	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		STARTING 1785.3 A A	
ALTITUDE		1000 m		EFFICIENCY	
HUMIDITY		80 %		AT 1/2 LOAD %	
AMBIENT TEMPERATURE		-10~40 °C		AT 3/4 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT FULL LOAD 95.0 %	
NEMA DESIGN		B		POWER FACTOR	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 1/2 LOAD %	
BEARING		TYPE BALL / BALL		AT 3/4 LOAD %	
		DEIN-DE NU320 / 6318C3		AT FULL LOAD 86.0 %	
		LUBRICANT GREASE		SPEED (AT FULL LOAD) 1180 rpm	
COUPLING METHOD		<input type="checkbox"/> DIRECT <input checked="" type="checkbox"/> V-BELT		TORQUE	
ROTATION(Facing Drive End)		<input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		FULL LOAD 132.0 kg-m 100%	
SHAFT		LOCKED ROTOR 118.8 kg-m 90%			
EXTENSION		SINGLE		BREAKDOWN 211.2 kg-m 160%	
EXTERNAL THRUST		-		NOISE LEVEL 86.0 dB(A)	
TERMINAL BOX		VIBRATION 30.0 μm			
MAIN		<input type="checkbox"/> STEEL <input type="checkbox"/> AL <input checked="" type="checkbox"/> CAST		ALLOWABLE LOAD GD² REFERRED TO MOTOR SHAFT	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		(AT DIRECT ON-LINE) - kg-m²	
BOX LOCATION		TOP (Viewed from Drive end)		Motor GD² - kg-m²	
APPLICATION STANDARDS		KS.IEC		MOTOR APPROX. WEIGHT 1,200 kg	
				PAINTING MUNSELL NO. 5PB 8.0/2.5	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-KMH215HU8P		
WINDING			SPEED-TORQUE CURVE ST-KMH215HU8P		
TYPE			TERMINAL BOX DIMENSION TB-315SM-1		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			2. HIGH EFFICIENCY MOTOR.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE					
IN ACCORDANCE WITH HIGEN MOTOR STANDARD.					
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE	
FC : FAN COOLED		SC : SELF COOLED		2015-08-24	
				PREPARED C.W.KIM	
				CHECKED S.S.YUN	
				APPROVED T.I.PARK	