



INDUCTION MOTOR DATA SHEET

3.7 kW 2 P FF215

MODEL: KMH-05HK3		CUSTOMER :		COIL SPEC NO.:		REV. NO : 0	
APPLICATION:		PROJECT NAME:			QUANTITY : SETS		
GENERAL DATA				PERFORMANCE DATA			
FRAME NO.		FF215		OUTPUT		3.7 kW	
ENCLOSURE		☐ DRIP PROOF		POLES		2 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE		SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		STARTING METHOD		☒ D.O.L ☐ Y-	
PROTECTION		☐ REACTOR (%TAP) ☐ V.V.V.F					
METHODS OF COOLING		☐ VECTOR-DRIVE					
PHASE		3 PHASE		RATED VOLTAGE		220 V 380 V	
SERVICE FACTOR		1.15		FREQUENCY		60 Hz	
INSULATION CLASS		F CLASS		CURRENT			
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD		A A	
				FULL LOAD		12.5 A 7.2 A	
				STARTING		112.2 A 65.0 A	
LOCATION		☒ INDOOR ☐ OUTDOOR		EFFICIENCY			
ALTITUDE		1000 m		AT 1/2 LOAD		%	
HUMIDITY		80 %		AT 3/4 LOAD		%	
AMBIENT TEMPERATURE		-10~40		AT FULL LOAD		87.5 %	
RATING		☒ CONT. ☐ %ED		POWER FACTOR			
NEMA DESIGN		B		AT 1/2 LOAD		%	
MOUNTING		☐ B3 ☒ B5 ☒ V1 ☐ B3B5		AT 3/4 LOAD		%	
BEARING		TYPE		BALL / BALL		AT FULL LOAD	
		DEIN-DE		6207ZZ / 6205ZZ		89.0 %	
		LUBRICANT		GREASE		SPEED (AT FULL LOAD)	
COUPLING METHOD		☒ DIRECT ☐ V-BELT		TORQUE			
ROTATION(Facing Drive End)		☐ CW ☒ CCW		FULL LOAD		1.03 kg-m 100%	
SHAFT				LOCKED ROTOR		1.65 kg-m 160%	
				BREAKDOWN		2.06 kg-m 200%	
		EXTENSION		SINGLE		NOISE LEVEL	
EXTERNAL THRUST		-		VIBRATION		80.0 dB(A)	
TERMINAL BOX				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
MAIN		☒ STEEL ☐ AL ☐ CAST		(AT DIRECT ON-LINE)		3.3 kg-m ²	
AUX.		☐ YES ☒ NO		Motor GD ²		0.057 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT		50 kg	
APPLICATION STANDARDS		KS.IEC		PAINTING		MUNSELL NO. 5PB 2.5 / 8	
				THICKNESS		☒ STANDARD ☐ μm	
ACCESSORIES (OPTIONAL)				SUBMITTAL DRAWINGS			
TEMPERATURE DETECTOR				OUTLINE DIMENSION		DW-KMH-05HK3F	
WINDING				TERMINAL BOX DIMENSION		TB-KMH-05HK3F	
				SPEED-TORQUE CURVE		ST-KMH-05HK3F	
BEARING							
TYPE							
SPACE HEATER							
RATING							
NOTE				REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE				1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.				2. HIGH EFFICIENCY MOTOR.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE							
IN ACCORDANCE WITH HIGEN MOTOR STANDARD.							
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE		PREPARED	
FC : FAN COOLED		SC : SELF COOLED		2015-07-13		S.D.YUN	
				CHECKED		APPROVED	
				S.D.YUN		K.I.HA	