

HIGEN		INDUCTION MOTOR DATA SHEET		15 HP - 4 P	
MODEL: KMH-15HU1F		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		FF300		OUTPUT 11 kW 15 HP	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 4 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-△	
PROTECTION		IP 54		STARTING METHOD <input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> SOFT-STARTER	
FREQUENCY		60 Hz		RATED VOLTAGE 380 V V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.15		NO LOAD 9.9 A A A	
INSULATION CLASS		F CLASS		FULL LOAD 22.5 A A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 189.3 A A A	
RES. METHOD		105 °C		EFFICIENCY	
THERMO. METHOD		°C		AT 1/2 LOAD %	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 91.0 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40 °C		AT 1/2 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 81.5 %	
MOUNTING		<input type="checkbox"/> B3 <input checked="" type="checkbox"/> B5 <input checked="" type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 1750 rpm	
BEARING		TYPE BALL		TORQUE	
		DEW-DE 6309ZZ / 6307ZZ		FULL LOAD 6.1 kg-m 100%	
		LUBRICANT GREASE		LOCKED ROTOR 11.6 kg-m 190%	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN 13.5 kg-m 220%	
SHAFT				NOISE LEVEL 78.0 dB(A)	
EXTENSION		SINGLE		VIBRATION 30.0 μm	
EXTERNAL THRUST				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
TERMINAL BOX				(AT DIRECT ON-LINE) 37.8 kg-m ²	
MAIN		<input type="checkbox"/> STEEL <input type="checkbox"/> AL <input checked="" type="checkbox"/> CAST		Motor GD ² 0.2869 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 122.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING MUNSSELL NO. 5 PB 6/1.5	
APPLICATION STANDARDS		KS.IEC		THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-V-160M-CAT		
WINDING			S-T CURVE ST-KMH-15HU1		
TYPE			TERMINAL BOX DIMENSION TB-3040KK2003		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN STANDARD.			2. HIGH EFFICIENCY MOTOR		
FC : FAN COOLED SC : SELF COOLED			DATE PREPARED CHECKED APPROVED		
			2008-05-02 J.S.PARK J.S.PARK H.T.KIM		