

HIGEN		INDUCTION MOTOR DATA SHEET		7.5 HP - 8 P	
MODEL:		CUSTOMER :		REV. NO : 0	
APPLICATION: KMI-08HK9F		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		FF300		OUTPUT 5.5 kW 7.5 HP	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 8 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-	
PROTECTION		IP 44		<input type="checkbox"/> REACTOR ( %TAP) <input type="checkbox"/> V.V.V.F	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> SOFT-STARTER	
PHASE		3 PHASE		RATED VOLTAGE 220 V 380 V V	
SERVICE FACTOR		1.15		FREQUENCY 60 Hz	
INSULATION CLASS		F CLASS		CURRENT	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD 17.0 A 9.8 A A	
RES. METHOD		105		FULL LOAD 26.9 A 15.5 A A	
THERMO. METHOD				STARTING 117.8 A 68.0 A A	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		EFFICIENCY	
ALTITUDE		1000 m		AT 1/2 LOAD %	
HUMIDITY		90 %		AT 3/4 LOAD %	
AMBIENT TEMPERATURE		-10-40		AT FULL LOAD 80.0 %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		POWER FACTOR	
NEMA DESIGN		B		AT 1/2 LOAD %	
MOUNTING		<input type="checkbox"/> B3 <input type="checkbox"/> B5 <input checked="" type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 3/4 LOAD %	
BEARING		TYPE BALL		AT FULL LOAD 67.0 %	
		DEW-DE 6309ZZ/6307ZZ		SPEED (AT FULL LOAD) 869 rpm	
		LUBRICANT GREASE		TORQUE	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		FULL LOAD 6.2 kg-m 100%	
ROTATION(Facing Drive End)		<input checked="" type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		LOCKED ROTOR 8.0 kg-m 130%	
SHAFT				BREAKDOWN 11.1 kg-m 180%	
EXTENSION		SINGLE		NOISE LEVEL 67.0 dB(A)	
EXTERNAL THRUST				VIBRATION 30.0 $\mu$ m	
TERMINAL BOX				ALLOWABLE LOAD GD <sup>2</sup> REFERRED TO MOTOR SHAFT	
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		(AT DIRECT ON-LINE) 91.0 kg-m <sup>2</sup>	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		Motor GD <sup>2</sup> 0.4933 kg-m <sup>2</sup>	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT 131.0 kg	
APPLICATION STANDARDS		IEC.KS		PAINTING	
				MUNSELL NO. 7.1 B 4.0/0.9	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> $\mu$ m	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR					
WINDING					
TYPE					
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE	PREPARED
FC : FAN COOLED		SC : SELF COOLED		2006-06-21	B.K.KIM
				CHECKED	APPROVED
				J.S.PARK	H.T.KIM