

HIGEN		INDUCTION MOTOR DATA SHEET		4 HP - 8 P	
MODEL: I04HK9FAOR		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		132S		OUTPUT 3.0 kW 4 HP	
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES 8 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof		<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y- <input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F <input type="checkbox"/> SOFT-STARTER		
PROTECTION		IP 54		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input type="checkbox"/> FC <input checked="" type="checkbox"/> AO			
FREQUENCY		60 Hz		RATED VOLTAGE 220 V 380 V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.0		NO LOAD 7.9 A 4.6 A A	
INSULATION CLASS		F CLASS		FULL LOAD 15.5 A 8.9 A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 100.8 A 58.2 A A	
RES. METHOD		105		EFFICIENCY	
THERMO. METHOD				AT 1/2 LOAD %	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 78.0 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40		AT 1/2 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 60.0 %	
MOUNTING		<input type="checkbox"/> B3 <input checked="" type="checkbox"/> B5 <input checked="" type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 850 rpm	
BEARING	TYPE	BALL		TORQUE	
	DEW-DE	6208ZZ/6206ZZ		FULL LOAD 3.4 kg-m 100%	
	LUBRICANT	GREASE		LOCKED ROTOR 6.2 kg-m 180%	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN 6.9 kg-m 200%	
SHAFT				NOISE LEVEL 65.0 dB(A)	
EXTENSION		SINGLE		VIBRATION 30.0 μ m	
EXTERNAL THRUST				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
TERMINAL BOX				(AT DIRECT ON-LINE) 42.9 kg-m ²	
MAIN		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> CAST		Motor GD ² 0.1530 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 61.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING MUNSELL NO. 7.1 B 4.0/0.9	
APPLICATION STANDARDS		KS.IEC		THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μ m	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR					
WINDING			NO		
TYPE					
BEARING			NO		
TYPE					
SPACE HEATER			NO		
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
FC : FAN COOLED SC : SELF COOLED			DATE PREPARED CHECKED APPROVED		
AO : AIR OF COOLING			2006-09-21 J.H JO J.S.PARK H.T.KIM		