

HIGEN		INDUCTION MOTOR DATA SHEET		20 HP - 6 P	
MODEL: KMI-20HT8		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		180M		OUTPUT 15 kW 20 HP	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 6 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-	
PROTECTION		IP 44		STARTING METHOD <input type="checkbox"/> REACTOR ( %TAP) <input type="checkbox"/> V.V.V.F	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> SOFT-STARTER	
FREQUENCY		50 Hz		RATED VOLTAGE 220 V 380 V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.0		NO LOAD 23.0 A 13.3 A A	
INSULATION CLASS		F CLASS		FULL LOAD 53.9 A 31.1 A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 361.4 A 208.6 A A	
RES. METHOD		105		EFFICIENCY	
THERMO. METHOD				AT 1/2 LOAD %	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 89.0 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40		AT 1/2 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 82.0 %	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 975 rpm	
BEARING		TYPE BALL		TORQUE	
		DEW-DE 6311ZZ/6309ZZ		FULL LOAD 15.0 kg-m 100%	
		LUBRICANT GREASE		LOCKED ROTOR 27.0 kg-m 180%	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN 30.0 kg-m 200%	
SHAFT				NOISE LEVEL 74.0 dB(A)	
EXTENSION		SINGLE		VIBRATION 30.0 $\mu$ m	
EXTERNAL THRUST				ALLOWABLE LOAD GD <sup>2</sup> REFERRED TO MOTOR SHAFT	
TERMINAL BOX				(AT DIRECT ON-LINE) 169.0 kg-m <sup>2</sup>	
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		Motor GD <sup>2</sup> 1.0462 kg-m <sup>2</sup>	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 166.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING MUNSELL NO. 7.1 B 4.0/0.9	
APPLICATION STANDARDS		KS.IEC		THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> $\mu$ m	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-H-180M-CA		
WINDING			S-T CURVE ST-KMI-20HT8		
TYPE			TERMINAL BOX DIMENSION TB-2M95115		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
FC : FAN COOLED SC : SELF COOLED			DATE PREPARED CHECKED APPROVED		
			2007.07.04 B.K.KIM J.S.PARK H.T.KIM		