

HIGEN		INDUCTION MOTOR DATA SHEET		22 KW - 4 P	
MODEL: KMI-30HE8		CUSTOMER :		REV. NO :	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.	180L		OUTPUT	22 kW	30 HP
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES	6 POLES	
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE	SQUIRREL CAGE	
	<input type="checkbox"/> Increased Safety Exp.-proof		STARTING METHOD	<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-	
PROTECTION	IP 44			<input type="checkbox"/> REACTOR ( %TAP) <input type="checkbox"/> V.V.V.F	
METHODS OF COOLING	<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>			<input type="checkbox"/> VECTOR DRIVE	
PHASE	3 PHASE		RATED VOLTAGE	415 V	V V
SERVICE FACTOR	1.0		FREQUENCY	50 Hz	
INSULATION CLASS	F CLASS		CURRENT		
TEMP. RISE AT FULL LOAD (at S.F 1.0)			NO LOAD	20.0 A	A A
RES. METHOD 105			FULL LOAD	42.0 A	A A
THERMO. METHOD			STARTING	294.0 A	A A
LOCATION	<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		EFFICIENCY		
ALTITUDE	1000 m		AT 1/2 LOAD %		
HUMIDITY	80 %		AT 3/4 LOAD %		
AMBIENT TEMPERATURE	-10~40		AT FULL LOAD 91.0 %		
RATING	<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		POWER FACTOR		
NEMA DESIGN	B		AT 1/2 LOAD %		
MOUNTING	<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 3/4 LOAD %		
BEARING	TYPE	BALL	AT FULL LOAD 80.0 %		
	DEW-DE	6312ZZ/6309ZZ	SPEED (AT FULL LOAD) 975 rpm		
	LUBRICANT	GREASE	TORQUE		
COUPLING METHOD	<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		FULL LOAD 22.0 kg-m 100%		
ROTATION(Facing Drive End)	<input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		LOCKED ROTOR 37.4 kg-m 170%		
SHAFT			BREAKDOWN 48.3 kg-m 220%		
EXTENSION SINGLE			NOISE LEVEL 79 dB(A)		
EXTERNAL THRUST			VIBRATION 30.0 $\mu$ m		
TERMINAL BOX			ALLOWABLE LOAD GD <sup>2</sup> REFERRED TO MOTOR SHAFT		
MAIN <input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST			(AT DIRECT ON-LINE) 247.0 kg-m <sup>2</sup>		
AUX. <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO			Motor GD <sup>2</sup> 1.1909 kg-m <sup>2</sup>		
BOX LOCATION LEFT (Viewed from Drive end)			MOTOR APPROX. WEIGHT 210 kg		
APPLICATION STANDARDS KS.IEC			PAINTING	MUNSELL NO.	7.1B 4.0/0.9
				THICKNESS	<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> $\mu$ m
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
			OUTLINE DIMENSION		
			SPEED-TORQUE CURVE		
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.					
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE					
IN ACCORDANCE WITH OTIS STANDARD.					
TE : TOTALLY ENCLOSED DP : DRIP PROOF		DATE	PREPARED	CHECKED	APPROVED
FC : FAN COOLED SC : SELF COOLED		2008-12-05	D.H.KAM	S.S.YUN	H.T.KIM